



## Attn: Purchasers of **DELPHI/SYSTech** Test Equipment

### Activation Procedures for Low Pressure Fuel Evaporative Tester (LPFET)

Follow these steps to activate your EVAP tester and to ensure it is ready to perform the official vehicle evaporative emissions test.

**STEP I**      **Call Delphi/SysTech Customer Support**  
**Delphi/Systech Call Center hours have been extended to:**  
**Monday thru Friday 8:00 AM to 6:00 PM (thru 12/7/07)**  
**Saturdays 8:00 AM to 5:00 PM (thru 12/1/07)**

1. Call Customer Support at **1-877-463-3574**.
2. Customer Support personnel will verify your facility information.
3. Customer Support personnel will enter your Smog Check Station License Number (Station ID) and Evap Tester Serial Number (Unit ID is the Serial Number Label of the tester and it is located on the back side of the tester) **into the Data Depot**.
4. Customer Support personnel will provide you the available Data Depot phone number for your area.
5. Customer Support personnel will register your EVAP tester in the Data Depot.

**STEP II**      **Connect to the Data Depot**

1. After Delphi/SysTech has registered your EVAP tester in the Data Depot, enter the Data Depot phone number (provided by Delphi/SysTech Customer Support) into your EVAP tester. (Note: Detailed instructions on how to enter the Data Depot phone number in the EVAP tester are included in the manufacturer's LPFET Instruction Manual.)
2. From the "MAIN MENU," select "4" (Comm. /Upload) and press "CONTINUE."
3. The tester will dial out and communicate to the Data Depot.
4. When the communication session is complete, press "CONTINUE" to return to the "MAIN MENU."

**STEP III**      **Perform Calibration (You will need nitrogen and a regulator to perform this step.)**

1. From the "MAIN MENU" select "3" (Cal Check) and press "CONTINUE."
2. Per the manufacturer's LPFET Instruction Manual, connect the filler neck hose to the calibration tank and set the calibration device to "OFF," then press "CONTINUE".
3. Follow the on-screen instructions. (Note: Detailed instructions for calibrating the EVAP tester are included in the manufacturer's LPFET Instruction Manual.)
4. Complete the "Cal Check."
5. Return to the "MAIN MENU."

**STEP IV**      **Re-connect to the Data Depot**

1. From the "MAIN MENU," select "4" (Comm. /Upload) and press "CONTINUE."
2. The tester will dial out and communicate to the Data Depot.
3. If the communication is successful, the tester will download the calibration record to the Data Depot. (Note: It can take up to 10 minutes to complete the activation process. If communication to the Data Depot is not successful, then check for error messages.)
4. When the communication session is complete, press "CONTINUE" to return to the "MAIN MENU."